

DESCRIPTION:

ULTRA-SCRUB INTERIOR SEMI-LUSTRE WALL & TRIM PAINT is formulated to exacting standards using the finest ingredients available. This 100% acrylic product, on a properly prepared surface, will give you years and years of service life. Ultra-Scrub Interior W/P also contains nano-technology—a micronized high density wax, which enhances the water permeability and reduces water absorption. This nano-technology also enhances the stain and chemical resistance of the coating. Stains are more likely to be removed with common household cleaners when compared to typical quality paints.

Reprinted from National Paint and Coatings Association, Inc., FLAMMABILITY OF PAINT STUDY conducted by Southwest Research Institute, Project 3-3774-141. "We believe this study provides substantial evidence that conventional paints and coatings do not increase the flame spread of either non-flammable or flammable substrate upon which they are applied. It also indicates that any fuel contribution or smoke density increase is insignificant when compared with the contribution of the substrate itself."

SPECIAL CAUTIONS:

“WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop and a HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD(5323) or log on to www.epa.gov/lead”.

Keep packaged material from freezing. If material has been frozen, do not stir until completely thawed. If material, when stirred after thawing, is of uniform consistency and has a suitable viscosity with no lumps, it may be used.

Do not apply when surface, air or material temperature is below 50° F. (10° C.).

SURFACE PREPARATION:

GENERAL - Surface must be clean and dry. Remove all dirt, loose or peeling paint, wallcovering and paste, grease and/or any other surface contamination. Repair all nail holes, cracks or other surface imperfections with with appropriate patching material and allow to cure. Dull glossy surfaces by using appropriate grade sandpaper or a liquid surface preparation. All surfaces should be sanded smooth as needed. Prime all surfaces with a appropriate primer as recommended by your Paint Dealer. Refer to "**Surface Preparation Guide**" for more detailed instructions.

UNFINISHED SURFACES:

WOOD - Sand smooth and apply one coat of Primer Undercoat. After primer has dried overnight, putty nail holes and cracks, then spot-prime putty with primer. Again, allow the primer to dry overnight, sand lightly and topcoat.

MASONRY AND CONCRETE - If efflorescence or cement dust is present on masonry and concrete, it should be removed by etching with a 10% solution of muriatic (Hydrochloric acid) solution; wear protective goggles and rubber gloves. Flush off surface, after etching, with clean water and allow to dry.

On surfaces where muriatic acid cannot be used to neutralize the efflorescence, sand, scrape, and wire brush and coat with Masonry Conditioner before painting.

Prime with latex primer and allow to dry four hours before topcoating. Rough concrete and haydite blocks should be filled with Latex Block Filler. Allow to dry overnight before priming.

PLASTER AND WALLBOARD - Prime with latex primer and allow to dry four hours before topcoating.

IRON AND STEEL - Prime with metal primer and allow to dry overnight before topcoating.

ULTRA-SCRUB INTERIOR WALL & TRIM PAINT – SEMI-LUSTRE 4-18

DESCRIPTION:

ULTRA-SCRUB INTERIOR SEMI-LUSTRE WALL & TRIM PAINT is formulated to exacting standards using the finest ingredients available. This 100% acrylic product, on a properly prepared surface, will give you years and years of service life. Ultra-Scrub Interior W/P also contains nano-technology—a micronized high density wax, which enhances the water permeability and reduces water absorption. This nano-technology also enhances the stain and chemical resistance of the coating. Stains are more likely to be removed with common household cleaners when compared to typical quality paints.

Values based on **ULTRA-SCRUB Interior Semi-Lustre Wall & Trim Paint**
5021 White, 5022 Tint Base, 5023 Deep Base, 5024 Accent Base

Weight Gallon: 10.27

Weight Solids: 46.5%

Volume Solids: 34.7%

Coverage:

@ 1 Dry Mil: 557 sq. ft./gallon

@ Spread Rate: 400 sq. ft./gallon (4.0 mils wet)

Deposits a 1.4 mil dry film

VOC (g/l): Not to Exceed 380

Viscosity: 100-105 K.U. @ 77° F.

Gloss @ 60: 45-55

Grind (Hegman): #6.5

DOT Class: Non-Combustible, Not Regulated

Federal Specification: TT-P-29 Performance Alternate

HMIS/NFPA: 1,0,0

Cure Time (Based on 70° F. & 50% R.H.):

To Touch: 30 Minutes

To Recoat: 2 Hours

Recommended Thinner: Water for clean-up and reduction for spray

Temperature Resistance: Continuous 150° F., Intermittent 200° F.

CAUTION! Do not take internally. Close container after each use. Use only with adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.** For specific safety requirements, refer to the Material Safety Data Sheet. Protect from freezing.

LIMITATION OF LIABILITY: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance, but is subject to change without prior notice. We make no guarantee of any kind, express or implied, including merchantability and fitness for particular purposes. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor, or cost of labor, and other consequential damages are hereby excluded.