



## DESCRIPTION:

A vinyl acrylic latex paint for laying down lines on all kinds of athletic fields and sports areas including football fields, baseball diamonds, soccer fields and running tracks. It is ready to use, safe and very easy to apply and contains no lime. When properly used, it is harmless to grass and participants and long lasting without blurring or dusting.

Values based on **Latex Field Marking Paint, 0720**

Weight Gallon:	11.58
Weight Solids:	47.8%
Volume Solids:	27.6%
Coverage:	
@ 1 Dry Mil:	443 sq. ft./gallon
@ Spread Rate:	400 sq. ft./gallon (4.0 mils wet) Deposits a 1.1 mil dry film
VOC (g/l):	Not to Exceed 250
Viscosity:	95-100 K.U. @ 77° F.
Gloss @ 60:	5 Max
Grind (Hegman):	#4-5
DOT Class:	Non-Combustible, Not Regulated
HMIS/NFPA:	1,0,0
Cure Time (Based on 70° F. & 50% R.H.):	
To Touch:	30 Minutes
To Recoat:	2 Hours

Recommended Thinner: Water for clean-up and reduction for spray

Temperature Resistance: Continuous 150° F., Intermittent 200° F.

**CAUTION!** Do not take internally. Close container after each use. Use only with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN. For specific safety requirements, refer to the Material Safety Data Sheet. Protect from freezing.

LIMITATION OF LIABILITY: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance, but is subject to change without prior notice. We make no guarantee of any kind, express or implied, including merchantability and fitness for particular purposes. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor, or cost of labor, and other consequential damages are hereby excluded.