

DESCRIPTION:

A vinyl acrylic latex paint for laying down lines on all kinds of athletic fields and sports areas including football fields, baseball diamonds, soccer fields and running tracks. It is ready to use, safe and very easy to apply and contains no lime. When properly used, it is harmless to grass and participants and long lasting without blurring or dusting.

SPECIAL CAUTIONS:

Keep packaged material from freezing. If material has been frozen, do not stir until completely thawed. If material, when stirred after thawing, is of uniform consistency and has a suitable viscosity with no lumps, it may be used.

Do not apply when surface, air or material temperature is below 50° F. (10° C.).

MIXING:

Stir each container thoroughly prior to use. No thinning is required for brush or roller application. For spray application, contingent upon equipment requirement, typically one pint to one quart of water per gallon of paint is all that is needed. However, do not exceed two parts water to one part paint.

APPLICATION:

Do not apply when surface, air or material temperature is below 50° F.

Stir contents before use. Apply using a brush, roller or striping machine. Keep brush or roller well filled and flow on freely. Allow 30 minutes for light traffic and 2 hours for normal traffic.

To spray, use the following recommendation or equal as a guide:

AIRLESS SPRAY:

Tip013-.017"
Fan 40°-60° (8-12 inch fan)
Pressure 1500-2000 PSI

CLEAN UP:

Clean brushes, rollers and spray equipment, after each use, with warm soapy water, then rinse with clean water. Follow-up with mineral spirits in spray equipment to avoid rusting. Dispose of used paint and waste in accordance with local, state and federal regulations.

COVERAGE:

One gallon will cover 200 square feet (600 lineal feet of 4 inch wide line), depending on surface roughness.

DRYING:

Optimum drying conditions are 60° F. to 90° F. (16° C. to 32° C.) at 50% R.H.

To Touch 30 Minutes
To Recoat 2 Hours

Lower temperatures and high humidity will slow dry.

LATEX FIELD MARKING PAINT

8-2

DESCRIPTION:

A vinyl acrylic latex paint for laying down lines on all kinds of athletic fields and sports areas including football fields, baseball diamonds, soccer fields and running tracks. It is ready to use, safe and very easy to apply and contains no lime. When properly used, it is harmless to grass and participants and long lasting without blurring or dusting.

Values based on **Latex Field Marking Paint, 0720**

Weight Gallon: 11.58

Weight Solids: 47.8%

Volume Solids: 27.6%

Coverage:

@ 1 Dry Mil: 443 sq. ft./gallon

@ Spread Rate: 400 sq. ft./gallon (4.0 mils wet)

Deposits a 1.1 mil dry film

VOC (g/l): Not to Exceed 100

Viscosity: 95-100 K.U. @ 77° F.

Gloss @ 60: 5 Max

Grind (Hegman): #4-5

DOT Class: Non-Combustible, Not Regulated

HMIS/NFPA: 1,0,0

Cure Time (Based on 70° F. & 50% R.H.):

To Touch: 30 Minutes

To Recoat: 2 Hours

Recommended Thinner: Water for clean-up and reduction for spray

Temperature Resistance: Continuous 150° F., Intermittent 200° F.

CAUTION! Do not take internally. Close container after each use. Use only with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN. For specific safety requirements, refer to the Material Safety Data Sheet. Protect from freezing.

LIMITATION OF LIABILITY: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance, but is subject to change without prior notice. We make no guarantee of any kind, express or implied, including merchantability and fitness for particular purposes. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor, or cost of labor, and other consequential damages are hereby excluded.